

## Datasheet for: 3PTS16309

### Product Type: 3P+N Isolating Delta Star

15kva 3P Delta Star 480v to 400v Hardwired



|                    |                                             |
|--------------------|---------------------------------------------|
| VA                 | 15000                                       |
| Input Voltage      | 480                                         |
| Input Termination  | M6 Brass studs                              |
| Input Current      | 18                                          |
| amps               | 21.7                                        |
| Output Voltage     | 400                                         |
| Output Notes       | Line to Line 400v Line to Neutral 230v      |
| Output Termination | M6 Brass studs                              |
| Product Case       | T3 Industrial floor/wall mounting case IP23 |
| Dimension          | Ht:500 L: 525 W:450 (mm)                    |
| Weight             | 95kg                                        |
| Product Type       | Isolating transformer                       |
| Standard           | Conforms to EN61558-2-6 CE & RoHS           |
| Regulation         | 3%                                          |

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



**Declaration of Conformity:** Airlink Transformers declare that the product 3PTS16309 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
30/08/2026

