


## Datasheet for: 3PHD10710

### Product Type: 3P Isolating Delta Delta

10kva 3P Delta Delta 400v to 208v Hardwired



VA	10000
Input Voltage	400
Input Termination	M5 Brass studs
Input Current	14.5
amps	28
Output Voltage	208
Output Termination	M5 Brass studs
Product Case	P6 Industrial floor/wall mounting case IP23
Dimension	Ht:454 L: 384 W:305 (mm)
Weight	65kg
Surge Protection	MS35 Surge Limiters
Product Type	Isolating transformer Conforms to EN61558-2-6 CE & RoHS
Regulation	4%

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product 3PHD10710 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
16/04/2026

