Datasheet for: 3PAD0115

Product Type: 3P+PE Auto Delta Delta

10kVA 3P 400-200v Hardwired



VA	10000
Input Voltage	400
Input Termination	Screw terminals
Input Current	14.44
amps	28.86
Output Voltage	200
Output Termination	Screw terminals
Product Case	P6 Industrial floor/wall mounting case IP23
Dimension	Ht:454 W:305 L:384
Weight	44kg
Surge Protection	SL32 Surge Limitor
Product Type	Autowound transformer Conforms to EN61558-2-13 CE & RoHS

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product 3PAD0115 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
29/11/2026

www.airlinktransformers.com - VAT No. 573 1888 10
Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS
01279 431865 | sales@airlinktransformers.com