

## Datasheet for: WM2264

### Product Type: Enclosed isolating transformers

2250VA 230v to 1x110v CTE & 1x 230v with 16amp sockets



|                    |                                                                 |
|--------------------|-----------------------------------------------------------------|
| VA                 | 2250                                                            |
| Input Voltage      | 230                                                             |
| Input Termination  | Screw terminals                                                 |
| Input Current      | 10                                                              |
| amps               | 16                                                              |
| Output Voltage     | 110v + 230v                                                     |
| Output Termination | 1x 110v 16amp yellow sockets & 1x 230v 16amp blue socket        |
| Product Case       | P3 Industrial floor/wall mounting case IP23                     |
| Dimension          | Ht:244 W:180 L:270                                              |
| Weight             | 15kg                                                            |
| Primary Protection | Push to reset circuit breaker SP12                              |
| Surge Protection   | SL32 Surge Limitor                                              |
| Product Type       | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS |
| Regulation         | 0.04                                                            |

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



**Declaration of Conformity:** Airlink Transformers declare that the product WM2264 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
30/08/2026

A handwritten signature in black ink, likely of the company representative.