



Datasheet for: WM5020

Product Type: Enclosed isolating transformers

5000VA 230v to 200v Hardwired



| | |
|--------------------|---|
| VA | 5000 |
| Input Voltage | 230 |
| Input Termination | Terminal Posts |
| Input Current | 22 |
| amps | 50 |
| Output Voltage | 200 |
| Output Termination | Terminal Posts |
| Product Case | P6 Industrial floor/wall mounting case IP23 |
| Dimension | Ht:454 L: 384 W:305 (mm) |
| Weight | 25kg |
| Primary Protection | Push to reset circuit breaker SP30 |
| Surge Protection | SL35 30A Surge limiter |
| Product Type | Safety Isolating transformer |
| Standard | Conforms to EN61558-2-06 CE & RoHS |
| Regulation | 0.02 |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product WM5020 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 16/04/2026



www.airlinktransformers.com - VAT No. 573 1888 10
Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS
01279 431865 | sales@airlinktransformers.com