Datasheet for: ST6000



Product Type: Heavy Duty 110v Portable transformers

6000VA 230v to 2x16A & 1x32A 110V SKT 5000VA Continuous Auto transformer

VA	6000
Input Voltage	230
Input Termination	2 meter mains lead (without plug)
Input Current	26
amps	32
Output Voltage	110
Output Notes	5000va continuous rating
Output Termination	2 x 16A & 1 x 32amp Yellow sockets
Product Case	801 Tough GRP case with carrying handle IP44
Dimension	Ht:280 W:340 D:260
Weight	26kg
Primary Protection	Push to reset circuit breaker SP30
Surge Protection	SL35 Surge Limiter
Product Type	Autowound transformer
Notes	This is an Autowound transformer 110v (No CTE Ground Centre Tap)

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product ST6000 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
29/11/2026

www.airlinktransformers.com - VAT No. 573 1888 10
Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS
01279 431865 | sales@airlinktransformers.com