# Datasheet for: CM0080207

## Product Type: Standard Range Toroidal Transformers

80VA 230v to 2x7v



| | |
|---|---|
| VA | 80 |
| Input Voltage | 230 |
| Input Termination | 200mm Flexible leads 22AWG |
| Input Current | 0.35 |
| amps | 5.7 |
| Output Voltage | 7+7 |
| Output Termination | 200mm Flexible leads 16AWG |
| Dimension | OD: 88 Ht: 36mm |
| Weight | 0.9kg |
| Product Type | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS |
| Regulation | 0.12 |
| Fixing | Hardware 2x 70mm Neoprene pads + steel dish washer with bolt |

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product CM0080207 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.
29/11/2026

www.airlinktransformers.com - VAT No. 573 1888 10
Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS
01279 431865 | sales@airlinktransformers.com