

Datasheet for: CM0120224

Product Type: Standard Range Toroidal Transformers

120VA 230V to 2x24V



VA	120
Input Voltage	230
Input Termination	200mm Flexible leads 18awg UL1015
Input Current	0.52
amps	2.5
Output Voltage	24+24
Output Termination	200mm Flexible leads 18awg UL1007
Dimension	OD: 88 Ht: 46mm
Weight	1.2kg
Product Type	Safety Isolating transformer
Standard	Conforms to EN61558-2-06 CE & RoHS
Regulation	0.11
Fixing	Hardware 2x 70mm Neoprene pads + steel dish washer with bolt

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product CM0120224 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
16/04/2026



